

RFID MIFARE CARDS



Mifare 1K is ISO/IEC 14443-A compliant which operates at 13.56 MHz and offers a typical read/write distance of 10 cm (4 inch) which can be used for more than 40 different types of applications worldwide. Some of its typical applications include but not limited to access control, identity, loyalty, public transport and events. These cards are available in 1K and 4K memory size. Our MIFARE Classic cards are manufactured with a glossy-white, print-quality PVC and/or composite (PET/PVC) material to support your imaging requirements. The cards are designed with highest precision and are individually tested to guarantee high performance. With a quickand lowest lead time we offer these cards at the most competitive and economic price in the industry.

PHYSICAL PARAMETER

Dimension	86mm x 54mm x 0.78mm
Printing	Yes. Both side.
Lamination	Yes. Both side.
Material	PVC/PET

RF SPECIFICATION

Protocol	ISO/IEC 14443-A
Operating Frequency	13.56 MHz
Read Range	Depends on chip & reader
IC Time	Mifare Classic (1K), Mifare Classic (4K), Mifare Ultralight, Mifare Ultralight Ev1,
IC Type	Mifare Ultralight C, Mifare DESfire, Mifare DESfire EV1, I Code SLIX.
Data Retention	10 Years
Anti-Collision	Yes
Working Mode	Read and Write

ENVIRONMENTAL SPECIFICATIONS

Operating Tempreture -25 °C to +70 °C

Storage Temperature -25 °C to +50 °C

Operating Humidity <=80%

ORDER INFORMATION

Part Number IDT.HF.MK

APPLICATION AREA







Education



Jewelry



Drug Management



Retail



