


# UHF RFID Inlay/Label IDT 9640



The IDT RFID 9640 Label/Inlay powered by the advanced Higgs-3 core, offers exceptional performance and a comprehensive set of features. With a 96 bits EPC memory bank, this tag provides efficient tracking, authentication, and serialization capabilities. Its 512 bits of user memory allow for distributed data applications, while password-protected read and write support ensure data security. The IDT 9640 Label/Inlay tag finds applications in various industries, including corrugate cases, pallet placards, apparel hang tags, baggage tags, shipping labels, asset management, and file folder labels. It is a versatile and reliable solution for enhancing tracking, inventory management, and data organization.

### PHYSICAL PARAMETERS

| Label Dimension             | 98mm x 12mm                                |  |
|-----------------------------|--|--|
| Antenna Dimension           | 94.8mm x 8.15mm                            |  |
| Adhesive                    | General Purpose Permanent                  |  |
| Interface Material          | "Paper, TT Printable White Film Overlay"   |  |
| Packaging                   | Premium Plastic Packing                    |  |
| Availability                | Dry/wet inlay                              |  |
| ENVIRONMENTAL SPECIFICATION |  |  |
| Operating Temperature       | -25°C to +50°C                             |  |
| Storage Temperature         | -25°C to +50°C                             |  |
| Chemical Resistance         | Resistant To Chemical Solvent and Moisture |  |
| Write Cycles                | 100,000                                    |  |
| Shelf Life                  | 2 years                                    |  |

# **RFID PERFORMACE**

| Working Frequency          | 865 – 868 MHz (ETSI) / 902 – 928 MHz (FCC) |
|----------------------------|--|
| Standard Protocol          | "ISO/IEC 18000-6C EPCglobal Class 1 Gen 2" |
| Chip Type                  | Alien Higgs-3                              |
| EPC Memory                 | 96 bits                                    |
| TID Memory                 | 64 bits                                    |
| Read Range Fixed Reader    | Up to 10m (Reader & Chip Dependent)        |
| Read Range Handheld Reader | Up to 8m (Reader & Chip Dependent)         |

# PERSONALIZATION

| Pre-Encoding       | Customer Specific Encoding of EPC                                     |
|--------------------|---|
| Customized Printed | Customer Specific Layout Including Logo, Text, Numbers, Barcode, etc. |

### ORDER INFORMATION

Part No.

IDT.RF.T.9640I.BL (Blank Inlay)

IDT.RF.T.9640L.BL (Blank Label)

#### **APPLICATION AREA**













Retail

Supply Chain

Warehouse

Manufaturing

Healthcare

Logistics



ID TECH SOLUTIONS PVT. LTD.

610, Udyog Vihar Phase-5, Gurgaon, Haryana - 122016, INDIA | T. : +91-124 - 4255530 (6 Lines) E.: info@idsolutionsindia.com | W: www.idsolutionsindia.com

