

# **UHF RFID DUO HANG TAG IDT DHT**













The RFID Duo Hang Tags (IDT DHT) are UHF Gen2 Long Range passive tags specifically designed for convenient attachment to assets with tying loops. These versatile tags offer a splendid reading range, making them highly beneficial for multiple industries. The RFID Duo Hang Tags are suitable for various applications, including apparel, IT assets, and hospital equipment. With the option for personalized printing and encoding, these tags can be tailored to meet specific requirements. Upgrade your tracking capabilities with the comprehensible and adaptable RFID Duo Hang Tags, improving efficiency across a wide range of industries.

#### **PARAMETERS**

Dimensions	120mm x 15mm
Weight	$5g \pm 1$
Encasement / Material	PET / PVC
Packaging	Premium Plastic Packing

## **ENVIRONMENTAL SPECIFICATION**


Operating Temperature	-40°C to +85°C
Storage Temperature	-40°C to +85°C
Chemical Resistance	Resistant To Chemical Solvent and Moisture
Shock & Vibration	MIL STD 810-G
Attachment	Nylon Thread, Lanyard
Sealing	IP 67

### **UHF PERFORMACE**

Working Frequency	865 – 868 MHz (ETSI) / 902 – 928 MHZ (FCC)
Standard Protocol	EPC C1 GEN2, ISO 18000-6C
Chip Type	Alien Higgs-3 /4, Monza 4/4QT/5/R6/R6P,UCODE 7/8 chip
EPC Memory	Chip Dependent

TID Memory	Chip Dependent
Read Range Fixed Reader	Up to 8m (Reader & Chip Dependent)
Read Range Handheld Reader	Up to 4m (Reader & Chip Dependent)

# TAG DIMENSION



### **PERSONALIZATION**

**Pre-Encoding** Customer Specific Encoding of EPC Customer Specific Layout Including Logo, Text, Numbers, Barcode, etc. **Customized Printed** 

### ORDER INFORMATION

IDT.RF.T.PHT.BL (Blank) Part No.

IDT.RF.T.PHT.WC (With Covering)

#### PPLICATION AREA









Logistics

Construction

Retail

Warehouse













